

View Online at <https://aerobasegroup.com/nsn/4720-00-997-6075>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.781 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded external tube 1st end

**Thready Qty Per Inch (tpi):**

18 1st end

**Burst Test Pressure:**

1600.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided fiber and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

400.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

30.0 degrees 1st end

**Hydrostatic Test Pressure:**

800.0 pounds per square inch

**Outer Covering Environmental Protection:**

Cold resistant and oil resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

13.250 inches

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Uns 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0