Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-997-6147

Cross Section	onal Shape:
Round	
Thread Class	s:
2b 1st end	
Thread Direc	ction:
Right-hand 1	st end
Inside Diame	eter:
0.375 inches	
Tempurature	e Rating:
-40.0 degrees	s fahrenheit and 200.0 degrees fahrenheit single response
Outside Diar	neter:
0.625 inches	
Connection	Style:
Swivel nut fla	ire 1st end
End Connec	tion Design:
Straight 1st e	Ind
Connection	Туре:
Threaded inte	ernal tube 1st end
Burst Test P	ressure:
1600.0 pound	ds per square inch
Layer Comp	osition And Location:
1st layer brai	ded rayon cord and outer layer molded rubber, synthetic
Maximum O	perating Pressure:
400.0 pounds	s per square inch
Thread Size:	
0.750 inches	1st end
Seat Angle:	
37.0 degrees	1st end
Hydrostatic	Test Pressure:
800.0 pounds	s per square inch
Outer Cover	ing Environmental Protection:
Oil resistant a	and weatherproof
Inside Surfa	ce Condition:
Smooth	
Measuring N	lethod And Length:
58.000 inche	S
Media For W	/hich Designed:
Fuel/oil, hydi	rocarbon single response
Thread Serie	es Designator:
Unf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0