

View Online at <https://aerobasegroup.com/nsn/4720-00-999-3794>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 225.0 degrees fahrenheit single response

Outside Diameter:

0.500 inches

Minimum Inside Bending Radius:

2.500 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j30, 30r2, type 1 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded external pipe 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

700.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

175.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

350.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant and oil resistant and water resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

42.000 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Specification Data:

Sae j30, 30r2, type 1 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0