Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-999-3905

Cross Sectional Shape:RoundFiread Class:2b 1st endThread Direction:Right-hand 1st endInside Diameter:0.250 inchesTempurature Rating:-6.0 degrees fahrenheit and 250.0 degrees fahrenheit single responseOutside Diameter:0.625 inchesConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endEnderdin Type:1threaded internal tube 1st endEnderdin Type:1threaded internal tube 1st endEnderdin Type:1threaded internal tube 1st endEnderdin Type:20 1st endBurst Test Pressure:11000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and outer layer molded rubberMaximum Operating Pressure:2750.0 pounds per square inchEnderdin Steel Steel wire and outer layer molded rubberMaximum Operating Pressure:2750.0 pounds per square inchEnderdin Steel St
Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Oty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
2b 1 st endThread Direction:Right-hand 1 st endInside Diameter:0.250 inchesTempurature Rating:-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single responseOutside Diameter:0.625 inchesConnection Style:Swivel nut flare 1 st endEnd Connection Design:Straight 2nd endConnection Type:1 Threaded internal tube 1 st endThreaded internal tube 1 st endEnset Pressure:1 1000.0 pounds per square inchLiaper Daried steel wire and outer layer molded rubberThreaded steel wire and outer layer molded rubber2750.0 pounds per square inch
Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Right-hand 1st endInside Diameter:0.250 inchesTempurature Rating:-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single responseOutside Diameter:0.625 inchesConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endEntready Gty Per Inch (tpi):20 1st endBurst Test Pressure:11000.0 pounds per square inchLayer Draided steel wire and outer layer molded rubberMaximum Operating Pressure:2750.0 pounds per square inch
Inside Diameter: 0.250 inches Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
0.250 inchesTempurature Rating:
Tempurature Rating:-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single responseOutside Diameter:0.625 inchesConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endThreaded internal tube 1st endBurst Test Pressure:11000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and outer layer molded rubber2750.0 pounds per square inch
 -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Oonection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Outside Diameter:0.625 inchesConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endThready Qty Per Inch (tpi):20 1st endBurst Test Pressure:11000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and outer layer molded rubberMaximum Operating Pressure:2750.0 pounds per square inch
0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
End Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endThready Qty Per Inch (tpi):20 1st endBurst Test Pressure:11000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and outer layer molded rubberMaximum Operating Pressure:2750.0 pounds per square inch
Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Thready Qty Per Inch (tpi):20 1st endBurst Test Pressure:11000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and outer layer molded rubberMaximum Operating Pressure:2750.0 pounds per square inch
20 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Burst Test Pressure:11000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and outer layer molded rubberMaximum Operating Pressure:2750.0 pounds per square inch
 11000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
1st layer braided steel wire and outer layer molded rubber Maximum Operating Pressure: 2750.0 pounds per square inch
Maximum Operating Pressure: 2750.0 pounds per square inch
2750.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
5500.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.075 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end

NSN 4720-00-999-3905

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

