NSN 4720-00-999-6466

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-999-6466

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
9.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber, synthetic and outer layer braided steel wire
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant and mildew resistant and oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

NSN 4720-00-999-6466

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0