Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-999-9852

	ape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.625 inches	
Tempurature Ratin	g:
-65.0 degrees fahre	nheit and 250.0 degrees fahrenheit single response
Outside Diameter:	
0.931 inches	
Connection Style:	
Swivel nut flare 1st	and
End Connection De	esign:
Straight 1st end	
Connection Type:	
Threaded internal tu	be 1st end
Thready Qty Per In	ch (tpi):
12 1st end	
Burst Test Pressur	e:
3000.0 pounds per s	quare inch
Layer Compositior	And Location:
2nd layer braided st	eel wire and 3rd layer molded rubber and 4th layer corrugated aluminum alloy and 5th layer corrugated copper and 6th
layer corrugated cor	rosion resistant steel
Maximum Operatin	g Pressure:
750.0 pounds per so	juare inch
Thread Size:	
1.062 inches 1st end	i de la constante de
Seat Angle:	
37.0 degrees 1st en	t de la constante de
Hydrostatic Test P	'essure:
1500.0 pounds per s	quare inch
Inside Surface Cor	dition:
Smooth	
Measuring Method	And Length:
86.125 inches	
Media For Which D	esigned:
Fuel/oil, hydrocarbo	n single response
Thread Series Des	gnator:
Un 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0