NSN 4720-00-999-9918

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-999-9918

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 0.406 inches and 0.438 inches
Minimum Inside Bending Radius:
1.500 inches
Exterior Color:
Black
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
1500.0 pounds per square inch
Layer Composition And Location:
1st layer braided rayon cord and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
375.0 pounds per square inch
Thread Size:
0.125 inches 1st end
Hydrostatic Test Pressure:
750.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
72.000 inches
Special Features:
Cadmium plated steel 1/8-27 npt thd female air hose quick disconnect coupling half assembled on one end
Test Data Document:
18876-10185886 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:

Npt 1st end

NSN 4720-00-999-9918

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0