NSN 4720-01-003-5468

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-003-5468 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.125 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.438 inches **Minimum Inside Bending Radius:** 1.750 inches **Exterior Color:** Black **Connection Style:** Inverted flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer rubber impregnated braided fabric and 2nd layer rubber impregnated braided fabric and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 13.625 inches

Unf 2nd end Shelf Life:

Thread Series Designator:

N/a

NSN 4720-01-003-5468

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0