NSN 4720-01-004-1420

Cross Sectional Shape:

Round

Smooth

Thread Class: 2b 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-004-1420

Right-hand 1st end
Inside Diameter:
1.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
2.125 inches
Minimum Inside Bending Radius:
20.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided textile yarn err-100
Maximum Operating Pressure:
175.0 pounds per square inch
Thread Size:
1.938 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
350.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and cold resistant and weatherproof
Inside Surface Condition:

NSN 4720-01-004-1420

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
51.000 inches
Special Features:
Inner conveying tube material-rubber, buna-n
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0