Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-004-7273

Crass Sectional Shane	
Cross Sectional Shape:	
Round Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.500 inches	
Minimum Inside Bending Radius:	
2.500 inches	
Connection Style:	
Plain 2nd end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external pipe 2nd end	
Burst Test Pressure:	
1600.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided fiber and outer layer molded rubber, chloroprene	
Maximum Operating Pressure:	
400.0 pounds per square inch	
Thread Size:	
0.250 inches 1st end	
Hydrostatic Test Pressure:	
800.0 pounds per square inch	
Outer Covering Environmental Protection:	
Oil resistant and ozone resistant and weatherproof	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
36.000 inches	
Thread Series Designator:	
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-01-004-7273

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

