

View Online at <https://aerobasegroup.com/nsn/4720-01-005-0631>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.420 inches

Temperature Rating:

-100.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

0.540 inches

Minimum Inside Bending Radius:

5.250 inches

Exterior Color:

Natural

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability and reusable end fittings

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

1st layer braided wire and 2nd layer braided fabric and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

16.500 inches

Special Features:

One protective guard to secure hose

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0