Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-005-2387

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 265.0 degrees fahrenheit single response	
Outside Diameter:	
0.500 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
1000.0 pounds per square inch	
Layer Composition And Location:	
1st layer molded rubber, synthetic and 2nd layer braided rayon cord and outer layer molded rubber, synthetic	
Maximum Operating Pressure:	
250.0 pounds per square inch	
Thread Size:	
0.437 inches 2nd end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
500.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
12.000 inches working	
Special Features:	
Furnished with dust caps	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 2nd end

Specification Data:

97424-4290w11 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0