## NSN 4720-01-005-5801

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-005-5801

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end Inside Diameter:
0.406 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 450.0 degrees fahrenheit single response  Outside Diameter:
0.500 inches
Minimum Inside Bending Radius: 4.625 inches
Connection Style: Swivel nut flare 2nd end
End Connection Design:
Straight 1st end  Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability  Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location: Outer layer braided steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch  Thread Size:
0.750 inches 2nd end
Seat Angle: 37.0 degrees 2nd end
·
Hydrostatic Test Pressure:
3000.0 pounds per square inch  Flow Angle:
-
90.0 degrees 2nd end Inside Surface Condition:
Smooth
Measuring Method And Length: 8 625 inches working
8.625 inches working  Throad Sories Designator:
Thread Series Designator:

Unjf 1st end

## NSN 4720-01-005-5801

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0