NSN 4720-01-005-6147

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-005-6147

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
Seat Angle: 30.0 degrees 1st end
30.0 degrees 1st end
30.0 degrees 1st end Hydrostatic Test Pressure:
30.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch
30.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch Outer Covering Environmental Protection:
30.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and mildew resistant and oil resistant and ozone resistant
30.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and mildew resistant and oil resistant and ozone resistant Vacuum In Torr:
30.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and mildew resistant and oil resistant and ozone resistant Vacuum In Torr: 50.0
30.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and mildew resistant and oil resistant and ozone resistant Vacuum In Torr: 50.0 Inside Surface Condition:
30.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and mildew resistant and oil resistant and ozone resistant Vacuum In Torr: 50.0 Inside Surface Condition: Smooth

Fuel/oil, hydrocarbon single response

NSN 4720-01-005-6147

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0