## NSN 4720-01-005-6148

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-005-6148

Cross Sectional Shape:
Round
Thread Class:
2b 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.560 inches
Minimum Inside Bending Radius:
12.000 inches
Connection Style:
Gasket seal / optional end 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal boss 2nd end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
1.500 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
180.000 inches
Media For Which Designed:

## NSN 4720-01-005-6148

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0