Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-006-5128

Cro	ss Sectional Shape:
Rou	nd
Thre	ead Class:
3b 1	st end
Thre	ead Direction:
Righ	nt-hand 1st end
Insi	de Diameter:
0.68	38 inches
Ten	npurature Rating:
-40.	0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Out	side Diameter:
0.93	38 inches
Min	imum Inside Bending Radius:
4.50	00 inches
Exte	erior Color:
Natu	ural
Con	nection Style:
Swiv	vel nut, flareless 2nd end
End	Connection Design:
Stra	ight 1st end
Con	inection Type:
Thre	eaded internal tube 1st end
Bur	st Test Pressure:
375	0.0 pounds per square inch
Lay	er Composition And Location:
2nd	layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Max	ximum Operating Pressure:
100	0.0 pounds per square inch
Thre	ead Size:
1.06	33 inches 2nd end
Sea	t Angle:
12.0) degrees 2nd end
Hyd	Irostatic Test Pressure:
200	0.0 pounds per square inch
Flov	w Angle:
45.0) degrees 2nd end
Insi	de Surface Condition:
Smo	poth
Mea	suring Method And Length:
48.2	250 inches working
Mec	lia For Which Designed:
F ue	I/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms87029 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0