NSN 4720-01-006-5129



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-006-5129 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.875 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 1.156 inches **Minimum Inside Bending Radius:** 5.500 inches **Exterior Color:** Natural **Connection Style:** Swivel nut, flareless 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 2500.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 750.0 pounds per square inch **Thread Size:** 1.313 inches 2nd end Seat Angle: 12.0 degrees 2nd end

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.500 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-006-5129

Nonmetallic Hose Assembly - Page 2 of 2



inread Series Designator:
Unjf 1st end
Specification Data:
96906-ms87029 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0