

View Online at <https://aerobasegroup.com/nsn/4720-01-006-7303>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.173 inches and 0.203 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

Between 0.296 inches and 0.328 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer spirally wrapped polytetrafluoroethylene fabric

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

90.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Fire resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.000 inches excluding end fittings

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0