## NSN 4720-01-007-1028

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-007-1028

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.750 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 235.0 degrees fahrenheit single response                      |
| Outside Diameter:  |
| 1.156 inches   |
| Minimum Inside Bending Radius:   |
| 9.500 inches   |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Thready Qty Per Inch (tpi):  |
| 12 1st end   |
| Burst Test Pressure:   |
| 9000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:  |
| 2250.0 pounds per square inch  |
| Thread Size:   |
| 1.062 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 4500.0 pounds per square inch  |
| Outer Covering Environmental Protection:   |
| Oil resistant and weatherproof   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 279.750 inches   |
| Media For Which Designed:  |

Fuel/oil, hydrocarbon single response

## NSN 4720-01-007-1028

Nonmetallic Hose Assembly - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Un 1st end                |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
|                           |

Demilitarization:

No

Fiig:

A542a0