

View Online at <https://aerobasegroup.com/nsn/4720-01-007-1936>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.968 inches

Minimum Inside Bending Radius:

7.000 inches

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting nickel alloy all ends

Connection Type:

Threaded external pipe 1st end

Features Provided:

Perforated outer cover and reusable end fittings

Second End Relationship With First End:

Identical

Burst Test Pressure:

14000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided wire err-100

Maximum Operating Pressure:

3500.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

7000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

120.000 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0