NSN 4720-01-007-8890

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-007-8890

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response
Outside Diameter:
0.469 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
1250.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.000 inches working

NSN 4720-01-007-8890

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Nitrogen, gaseous single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0