## NSN 4720-01-008-0776

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-008-0776

00			
Cross Sectional Shape:			
Round			
Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.250 inches			
Tempurature Rating:			
-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response			
Outside Diameter:			
0.500 inches			
Minimum Inside Bending Radius:			
4.000 inches			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
1250.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided cotton cord and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
200.0 pounds per square inch			
Thread Size:			
0.438 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
400.0 pounds per square inch			
Outer Covering Environmental Protection:			
Abrasion resistant and hydraulic solution resistant and oil resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
8.750 inches working			
Media For Which Designed:			
Fuel/oil, hydrocarbon single response			
Thread Series Designator:			
Unjf 1st end			

## NSN 4720-01-008-0776

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0