Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-008-2519

Cross Sectional Shap	e:
Round	
Thread Direction:	
Right-hand 2nd end	
Inside Diameter:	
0.212 inches	
Tempurature Rating:	
-67.0 degrees fahrenhe	it single response and 400.0 degrees fahrenheit single response
Outside Diameter:	
0.410 inches	
Minimum Inside Bend	ing Radius:
1.500 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut, flareless 1	t end
End Connection Desig	jn:
Straight 2nd end	
Connection Type:	
Threaded internal tube	1st end
Burst Test Pressure:	
12000.0 pounds per sq	uare inch
Layer Composition A	nd Location:
Outer layer braided wir	3
Maximum Operating I	Pressure:
3000.0 pounds per squ	are inch
Thread Size:	
10.000 millimeters 2nd	end
Seat Angle:	
12.0 degrees 2nd end	
Hydrostatic Test Pres	sure:
6000.0 pounds per squ	are inch
Inside Surface Condit	ion:
Smooth	
Measuring Method Ar	d Length:
12.750 inches working	
Thread Series Design	ator:
lso m 2nd end	
Shelf Life:	
N/a	
Unit Of Measure:	

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

