Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-008-3195

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Tempurature Rating:

-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.312 inches

Minimum Inside Bending Radius:

2.000 inches

Hose Or Tubing Specification/std Data:

Mil-h-27267, size 4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Ms27053-4c standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Nonmetallic Hose Assembly - Page 2 of 2



H	ydrostatic Test Pressure:
30	000.0 pounds per square inch
0	uter Covering Environmental Protection:
С	orrosion resistant
V	acuum In Torr:
50	0.8
In	side Surface Condition:
S	mooth
Μ	easuring Method And Length:
38	3.000 inches working and 38.500 inches working
S	pecial Features:
In	ner conveying tube material-plastic, polytetrafluoroethylene
Μ	edia For Which Designed:
F	uel/oil, hydrocarbon single response
T	hread Series Designator:
U	njf 1st end
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
Ν	0
Fi	iig:
A	542a0
Μ	il-std (military Standard):
М	il-h-27267 spec.