Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-008-3197

Cross	s Sectional Shape:
Round	t de la constante de
Threa	d Class:
3b 1st	tend
Threa	d Direction:
Right-	hand 1st end
Inside	e Diameter:
0.125	inches
Temp	urature Rating:
-65.0	degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Minim	num Inside Bending Radius:
1.500	inches
Conn	ection Style:
Swive	I nut flare 2nd end
End C	Connection Design:
Straig	ht 1st end
Conn	ection Type:
Threa	ded internal tube 1st end
Featu	res Provided:
Electr	ostatic discharge capability
Burst	Test Pressure:
12000	0.0 pounds per square inch
Layer	Composition And Location:
Outer	layer braided corrosion resistant steel wire
Maxin	num Operating Pressure:
1500.	0 pounds per square inch
Threa	ld Size:
0.375	inches 1st end
Seat /	Angle:
37.0 c	legrees 2nd end
Hydro	ostatic Test Pressure:
3000.	0 pounds per square inch
Flow	Angle:
90.0 c	legrees 2nd end
Outer	Covering Environmental Protection:
Corro	sion resistant
Vacu	um In Torr:
50.8	
Inside	e Surface Condition:
Smoo	th
	uring Method And Length:
27.00	0 inches working

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

