## NSN 4720-01-008-7197



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-008-7197 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.750 inches **Minimum Inside Bending Radius:** 5.500 inches **Exterior Color:** Orange **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 14 1st end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyamide cord and outer layer molded polyurethane **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.500 inches 2nd end Seat Angle: 45.0 degrees 2nd end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Inside Surface Condition:** Smooth

**Measuring Method And Length:** 38.500 inches

**Thread Series Designator:** 

Uns 1st end

## NSN 4720-01-008-7197

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0