## NSN 4720-01-009-2296

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

**Thread Direction:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-009-2296

Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
Between 0.304 inches and 0.343 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth

## NSN 4720-01-009-2296

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
72.000 inches working
Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms8000 government standard
Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A542a0