NSN 4720-01-009-2739

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-009-2739

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
Outside Diameter:
0.781 inches
Minimum Inside Bending Radius:
6.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
750.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
250.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant
Vacuum In Torr:
508.0
Inside Surface Condition:
Smooth
Measuring Method And Length:

35.000 inches working

NSN 4720-01-009-2739

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end
Specification Data:
88044-an6270-8d0350 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A542a0