## NSN 4720-01-009-3240

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-009-3240 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.344 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.543 inches **Minimum Inside Bending Radius:** 2.500 inches **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire, partial coverage and 2nd layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch **Outer Covering Environmental Protection:** Corrosion resistant **Vacuum In Torr:** 76.2

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

28.000 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

## NSN 4720-01-009-3240

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	-00.9.	

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0