## NSN 4720-01-009-9056

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-009-9056

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
Hydrostatic Test Pressure: 3000.0 pounds per square inch
•
3000.0 pounds per square inch
3000.0 pounds per square inch  Outer Covering Environmental Protection:
3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant
3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Vacuum In Torr:
3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Vacuum In Torr:  50.8
3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Vacuum In Torr:  50.8  Inside Surface Condition:

## NSN 4720-01-009-9056

Nonmetallic Hose Assembly - Page 2 of 2



inread Series Designator:
Unf 1st end
Specification Data:
96906-ms8000 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0