Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-011-4469

Cross Section	onal Shape:
Round	
Thread Direc	ction:
Right-hand 1	st end
Inside Diamo	eter:
0.500 inches	
Tempurature	e Rating:
	s fahrenheit and 200.0 degrees fahrenheit single response
Outside Dia	neter:
0.750 inches	
Minimum Ins	side Bending Radius:
5.000 inches	
Connection	Style:
Plain 2nd end	
End Connec	tion Design:
Straight 2nd	end
Connection	Туре:
Threaded ext	ernal pipe 2nd end
Burst Test P	ressure:
1000.0 pound	ds per square inch
Layer Comp	osition And Location:
1st layer brai	ded textile yarn and outer layer rubber impregnated braided cotton cord
Maximum O	perating Pressure:
250.0 pounds	s per square inch
Thread Size:	
0.750 inches	1st end
Outer Cover	ing Environmental Protection:
Cold resistan	t and mildew resistant and oil resistant
Inside Surfa	ce Condition:
Smooth	
Measuring M	lethod And Length:
14.875 inche	S
Media For W	hich Designed:
Fuel/oil, hyd	rocarbon single response
Thread Serie	es Designator:
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	ion:
No	

NSN 4720-01-011-4469

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

