Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-011-5561

Cros	ss Sectional Shape:
Rou	nd
Thre	ead Class:
3b 1	st end
Thre	ead Direction:
Righ	nt-hand 1st end
Insid	de Diameter:
0.18	7 inches
Tem	npurature Rating:
-65.0	0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outs	side Diameter:
0.51	6 inches
Mini	imum Inside Bending Radius:
3.00	0 inches
Con	nection Style:
Swiv	el nut with loose or integral clinch sleeve 1st end
End	Connection Design:
Strai	ight 1st end
Con	nection Type:
Thre	eaded internal tube 1st end
Burs	st Test Pressure:
1200	00.0 pounds per square inch
Laye	er Composition And Location:
Oute	er layer rubber impregnated braided cotton cord
Max	imum Operating Pressure:
3000	0.0 pounds per square inch
Thre	ead Size:
0.43	8 inches 1st end
Seat	t Angle:
12.0	degrees 1st end
Hyd	rostatic Test Pressure:
1000	0.0 pounds per square inch
Vac	uum In Torr:
50.8	i de la constante d
Insid	de Surface Condition:
Smo	poth
Mea	suring Method And Length:
12.0	00 inches
Thre	ead Series Designator:
Unf	1st end
She	If Life:
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0