

View Online at <https://aerobasegroup.com/nsn/4720-01-011-8255>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.625 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

0.980 inches

Minimum Inside Bending Radius:

3.250 inches

Hose Or Tubing Specification/std Data:

Sae j1403, type f-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

14 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

1000.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer rubber impregnated fabric err-100

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and light resistant and weatherproof

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

66.750 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Air single response and fuel/oil, hydrocarbon single response and water single response

Thread Series Designator:

Uns 1st end

Specification Data:

Sae j1403, type f-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0