## NSN 4720-01-012-5015

**Cross Sectional Shape:** 

Corrosion resistant

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-012-5015

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
End Application:
E-1c hawkeye aircraft
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.500 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:

## NSN 4720-01-012-5015

Nonmetallic Hose Assembly - Page 2 of 2



Criticality Code Justification:
Supp
nside Surface Condition:
Smooth
Measuring Method And Length:
42.000 inches working
Special Features:
Clean and package for oxygen service
Supplementary Features:
This item is a flight safety critical aircraft part
Thread Series Designator:
Jnjf 1st end
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A542a0