

View Online at <https://aerobasegroup.com/nsn/4720-01-012-6931>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.562 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nonskive

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided wire and 2nd layer braided fabric and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Outer Covering Environmental Protection:

Ozone resistant

Vacuum In Torr:

127.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

23.000 inches

Special Features:

One protective guard to secure hose

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0