NSN 4720-01-013-4588

Cross Sectional Shape:

Fuel/oil, hydrocarbon single response

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-013-4588

3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.406 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response			
Outside Diameter:			
0.562 inches			
Minimum Inside Bending Radius:			
4.625 inches			
Angle Between Rigid Elbow Fittings In Deg:			
180.0			
Connection Style:			
Swivel nut, inverted flare 2nd end			
End Connection Design:			
Elbow 2nd end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
7000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
1500.0 pounds per square inch			
Thread Size:			
0.750 inches 2nd end			
Seat Angle:			
45.0 degrees 2nd end			
Hydrostatic Test Pressure:			
3000.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
26.000 inches working			
Media For Which Designed:			

NSN 4720-01-013-4588

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	-00.9.	

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0