

View Online at <https://aerobasegroup.com/nsn/4720-01-013-5784>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.190 inches

Outside Diameter:

0.320 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Nut stainless steel all ends

Fitting Component And Surface Treatment:

Nut passivate 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

1st layer spirally laid corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.437 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

5000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Heat resistant

Measuring Method And Length:

33.375 inches working

Second End Swivel Action Capability:

Included

Outside Diameter Tube Accommodated:

0.320 inches 1st end

Special Features:

Inner conveying tube material-plastic

Media For Which Designed:

Nitrogen, gaseous single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0