

View Online at <https://aerobasegroup.com/nsn/4720-01-014-4439>

**Temperature Rating:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

**Flange Thickness:**

0.297 inches 1st end

**Recess Diameter:**

1.938 inches 1st end

**Recess Depth:**

0.168 inches 1st end

**Minimum Inside Bending Radius:**

7.500 inches

**Center To Center Distance Between Bolt Holes Along Width:**

1.812 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

1.812 inches 1st end

**Bolt Hole Quantity:**

4 1st end

**Flange Length:**

2.375 inches 1st end

**Flange Width:**

2.375 inches 1st end

**Connection Style:**

Recessed 1st end

**Bolt Hole Diameter:**

0.266 inches 1st end

**End Flange Construction:**

Solid 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Recessed flange 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

3000.0 pounds per square inch

**Layer Composition And Location:**

1st layer woven fabric and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

750.0 pounds per square inch

**Inside Surface Condition:**

Convuluted

**Measuring Method And Length:**

14.875 inches working and 15.125 inches working

**Flange Style:**

Rectangular (includes square) 1st end

**Special Features:**

2nd end c/o 1 collar; 1 adaptor, p/n x292-352; 1 polyethylene cap, p/n 93219-22

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0