

View Online at <https://aerobasegroup.com/nsn/4720-01-014-4440>

Cross Sectional Shape:

Round

Inside Diameter:

0.310 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Bolt Circle Diameter:

1.000 inches 2nd end

Outside Diameter:

0.450 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Natural

Bolt Hole Quantity:

2 2nd end

Connection Style:

Swivel nut, flareless 1st end

Bolt Hole Diameter:

0.256 inches 2nd end

Raised Face Height:

0.118 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nuts drilled for lockwire

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.875 inches working

Flange Style:

Oval 2nd end

Thread Series Designator:

Iso m 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0