## NSN 4720-01-015-4525

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-015-4525

View Online at https://aerobasegroup.com/nsn/4720-01-015-4525
Cross Sectional Shape:
Round
Inside Diameter:
1.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Flange Thickness:
0.297 inches 1st end
Outside Diameter:
1.792 inches
Recess Diameter:
2.760 inches 1st end
Recess Depth:
0.168 inches 1st end
Minimum Inside Bending Radius:
7.500 inches
Center To Center Distance Between Bolt Holes Along Width:
1.812 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
1.812 inches 1st end
Bolt Hole Quantity:
4 1st end
Flange Length:
2.375 inches 1st end
Flange Width:
2.375 inches 1st end
Connection Style:
Recessed 1st end
Bolt Hole Diameter:
0.266 inches 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Recessed flange 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
3000.0 pounds per square inch

**Layer Composition And Location:** 

1st layer woven fabric and outer layer braided corrosion resistant steel wire

## NSN 4720-01-015-4525

Nonmetallic Hose Assembly - Page 2 of 2



## Maximum Operating Pressure: 750.0 pounds per square inch Inside Surface Condition: Convoluted Measuring Method And Length: 18.125 inches Flange Style: Rectangular (includes square) 1st end Special Features: 2nd end c/o 1 collar; 1 adaptor; 1 polyethylene cap Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A542a0