NSN 4720-01-016-1385

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-016-1385 **Cross Sectional Shape:** Round **Inside Diameter:** 1.500 inches **Tempurature Rating:** -32.0 degrees celsius and 52.0 degrees celsius single response **Outside Diameter:** 2.125 inches **Exterior Color:** Black **Quick Disconnect Size:** 1.500 inches 2nd end **End Application:** 4930-00-426-9960 tank and pump unit **Connection Style:** Cam or lever (external) 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Internal quick disconnect 1st end **Features Provided:** Electrostatic discharge capability and reusable end fittings **Burst Test Pressure:** 500.0 pounds per square inch **Layer Composition And Location:** 1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided cotton cord and outer layer molded rubber, synthetic **Hydrostatic Test Pressure:** 150.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant and mildew resistant and ozone resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 39.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 4720-01-016-1385

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-370j spec.