## NSN 4720-01-016-2534

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-016-2534

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.250 inches
Tempurature Rating:
-650.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Flange Thickness:
0.315 inches 2nd end
Outside Diameter:
2.000 inches
Flange Outside Diameter:
2.000 inches 2nd end
Connection Style:
Plain w/ gasket groove (sae flanged head) 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
1625.0 pounds per square inch
Thread Size:
1.250 inches 1st end
Hydrostatic Test Pressure:
3250.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.000 inches
Flange Style:
Round w/ out bolt holes 2nd end

Fuel/oil, hydrocarbon single response

Media For Which Designed:

## NSN 4720-01-016-2534

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Nptf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0

Mil-std (military Standard):

Mil-dtl-13531 spec.