

View Online at <https://aerobasegroup.com/nsn/4720-01-016-8391>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.469 inches

**Exterior Color:**

Natural

**Hose Or Tubing Specification/std Data:**

Mil-h-13444, type 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting copper alloy 360 all ends

**Thready Qty Per Inch (tpi):**

24 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

1250.0 pounds per square inch

**Layer Composition And Location:**

Outer layer molded rubber, chloroprene err-100

**Maximum Operating Pressure:**

300.0 pounds per square inch

**Thread Size:**

0.500 inches 1st end

**Seat Angle:**

45.0 degrees 2nd end

**Hydrostatic Test Pressure:**

625.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

14.650 inches working and 15.000 inches working

**Second End Swivel Action Capability:**

Included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Uns 1st end

**Specification Data:**

Mil-h-13444, type 1 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-13444 spec.