

| NSN 4720-01-017-4297 Nonmetallic Hose Assembly - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/4720-01-017-4297 |
| Cross Sectional Shape: |
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.500 inches |
| Connection Style: |
| Plain optional end 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal pipe 1st end |
| Layer Composition And Location: |
| 1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 2nd end |
| Seat Angle: |
| 30.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Mildew resistant and oil resistant and oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 108.000 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Nptf 2nd end |
| Shelf Life: |

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4720-01-017-4297

Nonmetallic Hose Assembly - Page 2 of 2



Fiig: A542a0 Mil-std (military Standard):

Mil-dtl-13531 spec.