

View Online at <https://aerobasegroup.com/nsn/4720-01-018-1762>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.234 inches and 0.266 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.453 inches and 0.500 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j30b, 30r2, type 1-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

First End Fitting Specification/std Data:

Sae j516a, table 2-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Plain optional end 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Socket stainless steel 2nd end

Fitting Component And Surface Treatment:

Socket passivate 1st end

Connection Type:

Threaded internal pipe 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

1500.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

375.0 pounds per square inch

Thread Size:

0.125 inches 2nd end

Hydrostatic Test Pressure:

750.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and heat resistant and oil resistant and ozone resistant

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

50.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response and oil, lubricating, diester base single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0