

View Online at <https://aerobasegroup.com/nsn/4720-01-018-6550>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

Between 0.485 inches and 0.531 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.937 inches and 0.999 inches

**End Application:**

Truck, forklift, diesel engine driven, 6000 lb.; anthony model mlt 6-2, nsn 3930003271575; crane, wheel mtd; 20-ton w/blk tackle

**Burst Test Pressure:**

14000.0 pounds per square inch single response

**Layer Composition And Location:**

2nd layer braided corrosion resistant steel wire or 1st layer braided corrosion resistant steel wire or outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

3500.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

7000.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Oil resistant and ozone resistant

**Criticality Code Justification:**

Feat

**Inside Surface Condition:**

Smooth

**Special Features:**

Weapon system essential; inner conveying tube material: butadiene acrylnitrile rubber or chloroprene rubber

**Specification Or Standard:**

100r2 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A541z0

**Mil-std (military Standard):**

Mil-h-52471 spec.