

View Online at <https://aerobasegroup.com/nsn/4720-01-018-6550>

Cross Sectional Shape:

Round

Inside Diameter:

Between 0.485 inches and 0.531 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.937 inches and 0.999 inches

End Application:

Truck, forklift, diesel engine driven, 6000 lb.; anthony model mlt 6-2, nsn 3930003271575; crane, wheel mtd; 20-ton w/blk tackle

Burst Test Pressure:

14000.0 pounds per square inch single response

Layer Composition And Location:

2nd layer braided corrosion resistant steel wire or 1st layer braided corrosion resistant steel wire or outer layer molded rubber, chloroprene

Maximum Operating Pressure:

3500.0 pounds per square inch single response

Hydrostatic Test Pressure:

7000.0 pounds per square inch single response

Outer Covering Environmental Protection:

Oil resistant and ozone resistant

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Special Features:

Weapon system essential; inner conveying tube material: butadiene acrylnitrile rubber or chloroprene rubber

Specification Or Standard:

100r2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A541z0

Mil-std (military Standard):

Mil-h-52471 spec.