

View Online at <https://aerobasegroup.com/nsn/4720-01-018-9809>

Cross Sectional Shape:

Round

Inside Diameter:

1.120 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Flange Thickness:

0.296 inches 2nd end

Outside Diameter:

1.440 inches

Minimum Inside Bending Radius:

8.000 inches

Exterior Color:

Natural

Center To Center Distance Between Bolt Holes Along Width:

1.656 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.656 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.188 inches 2nd end

Flange Width:

2.188 inches 2nd end

Connection Style:

Plain swivel 1st end

Bolt Hole Diameter:

0.266 inches 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Plain face flange 2nd end

Features Provided:

Internal support

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

800.0 pounds per square inch

Hydrostatic Test Pressure:

1300.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

23.125 inches working

Flange Style:

Rectangular (includes square) 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon and water single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0