NSN 4720-01-019-2147

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-019-2147

Cross Sectional Shape:
Round
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and 2nd layer braided fabric and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
4000.0 pounds per square inch
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
700.0 pounds per square inch
Flow Angle:
45.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and corrosion resistant
Vacuum In Torr:
127.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
130.000 inches
Special Features:
One protective guard to secure hose
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-01-019-2147

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0