NSN 4720-01-019-8058

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-019-8058

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.406 inches				
Tempurature Rating:				
-67.0 degrees fahrenheit and 450.0 degrees fahrenheit single response				
Outside Diameter:				
0.562 inches				
Minimum Inside Bending Radius:				
4.562 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
6000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
1500.0 pounds per square inch				
Thread Size:				
0.750 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
3000.0 pounds per square inch				
Outer Covering Environmental Protection:				
Corrosion resistant and fuel resistant				
Inside Surface Condition:				
Smooth				

Thread Series Designator:

Media For Which Designed:

Measuring Method And Length:

Fuel/oil, hydrocarbon single response

188.348 inches working and 192.152 inches working

Unjf 1st end

NSN 4720-01-019-8058

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0